



Automation for a Changing World

Delta Industrial Automation

TEXT PANELS & HUMAN MACHINE INTERFACES

7-Inch Touch Panel HMI with Built-in PLC New

TP70P-RM0

- ▶ Adopts core of SS2 series PLC with program of 2K steps and D devices of 5K words
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload / download
- ▶ Built-in 2 sets of communication ports
- ▶ Supports MODBUS ASCII / RTU modes
- ▶ Built-in real time clock (RTC)

Dimensions	7" (154 x 85mm)
Resolution	800 x 480
Display Color	65535 colors
Flash Memory	64M bytes
SRAM	64k bytes
Function Keys	Not available
Password	Available
Recipe Function	Not available
Real-time Clock	Available
Serial COM Port	2 Sets of Communication ports
Editing Software	TPEditor

4 Line Text Panel HMI

TP04G-AL-C

TP04G-AL2

- ▶ 4.1" STN-LCD
- ▶ User-defined function keys available
- ▶ Supports RS-232/RS-422/RS-485 COM ports (TP04G-AL2)
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 x 35.24mm)
Resolution	192 x 64
Display Color	Monochrome
Flash Memory	256k bytes
SRAM	16k/10k bytes
Function Keys	10 function keys
Password	Available
Recipe Function	Not available
Real-time Clock	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

4 Line Text Panel HMI

TP04G-BL-C

- ▶ 4.1" STN-LCD
- ▶ 0 ~ 9 numeric keys and user-defined function available
- ▶ Built-in RS-232 and RS-422/RS-485 ports
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ Password protection function available
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)

Dimensions	4.1" (101.8 x 35.24mm)
Resolution	192 x 64
Display Color	Monochrome
Flash Memory	256k bytes
SRAM	10k bytes
Function Keys	17 function keys
Password	Available
Recipe Function	Not available
Real-time Clock	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

8 Line Text Panel HMI

TP08G-BT2

- ▶ 3.8" STN-LCD
- ▶ Resolution: 240 x 128 dots
- ▶ Built-in 1024KB flash memory
- ▶ 24 user-defined function keys
- ▶ Built-in RS-232 and RS-422/RS-485 COM ports
- ▶ Supports recipes and macro functions

Dimensions	3.8" (83mm x 41 mm)
Resolution	240 x 128
Display Color	Monochrome
Flash Memory	1M bytes
SRAM	64k bytes
Function Keys	24 function keys
Password	Available
Recipe Function	Available
Real-time Clock	Available
Serial COM Port	RS-232 & RS-422/485
Editing Software	TPEditor

7-Inch Touch Panel HMI with Built-in PLC New

TP70P

- ▶ Adopts core of SS2 series PLC with program of 4K steps and D devices of 5K words
- ▶ Provides 2 sets of 10kHz high speed pulse input
- ▶ 7" TFT-LCD
- ▶ Touch screen
- ▶ Built-in USB port for program upload / download
- ▶ Built-in 2 sets of communication ports
- ▶ Supports MODBUS ASCII / RTU modes
- ▶ Built-in real time clock (RTC)
- ▶ Digital and Analog I/O points available

Dimensions	7" (154 x 85mm)
Resolution	800 x 480
Display Color	65535 colors
Flash Memory	64M bytes
SRAM	64k bytes
Function Keys	Not available
Password	Available
Recipe Function	Not available
Real-time Clock	Available
Serial COM Port	2 sets of RS-485
Editing Software	TPEditor

4-Line Text Panel HMI with Built-in PLC

TP04P

- ▶ Adopts core of SS2 series PLC with program of 8K steps and D devices of 5K words
- ▶ Provides 2 sets of 10kHz high speed pulse input
- ▶ 4.1" STN-LCD
- ▶ Provides 0 ~ 9 numeric keys with user defined function
- ▶ Built-in USB port for program upload/download
- ▶ Built-in 2 sets of RS-485 communication port
- ▶ Supports MODBUS ASCII/RTU modes
- ▶ User-defined boot screen available
- ▶ Built-in real time clock (RTC)
- ▶ Digital and Analog I/O points available

Dimensions	4.1" (101.8 × 35.24mm)
Resolution	192 x 64
Display Color	Monochrome
Flash Memory	1M bytes
SRAM	64k bytes
Function Keys	17 function keys
Password	Available
Recipe Function	Not available
Real-time Clock	Available
Serial COM Port	2 sets for RS-485
Editing Software	TPEditor



High Color, High Resolution Human Machine Interfaces

4.3-inch Widescreen HMI

DOP-B03S(E)211

- ▶ 4.3" 16: 9 widescreen, 65536 colors TFT
- ▶ Display Resolution: 480 x 272 pixels
- ▶ Supports Ethernet
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad



5.6-inch HMI

DOP-B05S111

- ▶ 5.6" 65536 colors TFT
- ▶ Display Resolution: 320 x 234 pixels
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad



7-inch Widescreen HMI

DOP-B07S411 / DOP-B07S(E)415

- ▶ 7" 16: 9 widescreen, 65536 colors TFT
- ▶ Display Resolution: 800 x 480 pixels
- ▶ Supports Ethernet
- ▶ Supports SDHC card
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files



7-inch Widescreen HMI with Delta Professional Functions

DOP-B07PS415

- ▶ 7" 16: 9 widescreen, 65536 colors TFT
- ▶ Display Resolution: 800 x 480 pixels
- ▶ Supports SDHC card
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files
- ▶ Supports Electronic Cam (E-Cam) function (ASDA-A2)
- ▶ Supports G-Code download function (DVP-10MC / DVP-20PM / AH20MC)




»» DOP-B series

7-inch HMI with Delta Professional Functions

DOP-B07PS515

- ▶ 7" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ Supports SDHC card
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files
- ▶ Supports Electronic Cam (E-Cam) function (ASDA-A2)
- ▶ Supports G-Code download function (DVP-10MC / DVP-20PM / AH20MC)
- ▶ The world's first design: the effective display area is the same as 7-inch models, but the panel cutout's dimensions are just the same as 5.6-inch models.



7-inch HMI

DOP-B07S(E)515

- ▶ 7" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files
- ▶ The world's first design: the effective display area is the same as 7-inch models, but the panel cutout's dimensions are just the same as 5.6-inch models.
- ▶ Supports Ethernet
- ▶ Supports SDHC card



8-inch HMI

DOP-B08S(E)515


- ▶ 8" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files
- ▶ Supports Ethernet
- ▶ Supports SDHC card



10.1-inch Widescreen HMI

DOP-B10S411 / DOP-B10S(E)615

- ▶ 10.1" 16: 9 widescreen, 65536 colors TFT
- ▶ Display Resolution: 800 x 480 pixels/1024 x 600 pixels
- ▶ USB Client for high-speed data transfer
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports audio output: MP3, Wav files
- ▶ Supports Ethernet
- ▶ Supports SDHC card



10.4-inch HMI

DOP-B10S511 / DOP-B10E515

- ▶ 10.4" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ Supports audio output: MP3, Wav files
- ▶ Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports Ethernet
- ▶ Supports SDHC card



10.4-inch Large-Size HMI New

DOP-W105B

- ▶ 10.4" 65536 colors TFT LCD
- ▶ Display Resolution: 800 x 600 pixels
- ▶ 1GHz high speed processor
- ▶ Supports audio output (MP3, Wav files)
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports 2 Ethernet ports
- ▶ Supports SDHC card
- ▶ Supports video format: MPEG1, MPEG2, WMV



12-inch Large-Size HMI New

DOP-W127B

- ▶ 12" 65536 colors TFT LCD
- ▶ Display Resolution: 1024 x 768 pixels
- ▶ 1GHz high speed processor
- ▶ Aluminum enclosure with dark gray mold texturing
- ▶ 2 sets of COM ports, support RS232 / RS422 / RS485
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports 2 Ethernet ports
- ▶ Supports SDHC card
- ▶ Supports video format: MPEG1, MPEG2, WMV
- ▶ Supports audio output: MP3, Wav files (built-in front speaker)



15-inch Large-Size HMI New

DOP-W157B

- ▶ 15" 65536 colors TFT LCD
- ▶ Display Resolution: 1024 x 768 pixels
- ▶ 1GHz high speed processor
- ▶ Aluminum enclosure with dark gray mold texturing
- ▶ 2 sets of COM ports, support RS232 / RS422 / RS485
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad
- ▶ Supports 2 Ethernet ports
- ▶ Supports SDHC card
- ▶ Supports video format: MPEG1, MPEG2, WMV
- ▶ Supports audio output: MP3, Wav files (built-in front speaker)



»» HMC series

Optimum Combination of Display and Controller Controllers with Human Machine Interfaces

7-inch Controller with HMI, Handheld Type HMC07-N510(1)52

- ▶ 7" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ **Built-in PLC functions**
- ▶ RS-422 high-speed remote I/O connection
- ▶ Supports Ethernet
- ▶ Supports SDHC card
- ▶ Supports DMCNET
- ▶ Supports audio output: MP3, Wav files
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad




8-inch Controller with HMI HMC08-N500S52

- ▶ 8" 65536 colors TFT
- ▶ Display Resolution: 800 x 600 pixels
- ▶ **Built-in PLC functions**
- ▶ RS-422 high-speed remote I/O connection
- ▶ Supports MPG (Manual Pulse Generator) Input
- ▶ Supports Ethernet
- ▶ Supports SDHC card
- ▶ Supports DMCNET
- ▶ Supports audio output: MP3, Wav files
- ▶ USB Host for direct connection to USB disk, printer, mouse and keypad

High Quality
Full-Color DisplayEnergy Saving
Environmental Automation

A Wide Range of Options

Powerful Controller Drivers Support





Transmisiones Ltda. Carrera 68 B # 21 A –
24, bodega UE 28- 1 Parque Industrial
Montevideo PBX: (57+1) 4126898
Bogotá – Colombia
info@ transmisiones.de
www.transmisiones.de

*We reserve the right to change the information in this catalogue without prior notice.